



Nachfolgend sind die Standardeinstellung der Anlage „Openscape business X5“ des Herstellers UNIFY beschrieben. Für Telefonanlagen von anderen Herstellern können die Einstellungsoptionen leicht abweichend bzw. anders bezeichnet sein. Bitte kontaktieren Sie in diesem Fall den jeweiligen Hersteller ihrer TK-Anlage oder wenden Sie sich an einen Dienstleister für Telefon- und Kommunikationssysteme.

Konfigurationsbeispiel anhand einer Unify Openscape business X5

Provider Angaben

Provider-Name	WOBCOM GmbH
Provider aktivieren	Yes / ✓
Providerzeichner im System	Richtung 12
Gateway Domain Name	62.176.255.210
Transportprotokoll	udp
Transportsicherheit	traditional (udp or tcp)

Provider Registrar

Provider Registrar verwenden	Yes / ✓
IP Adresse/Host-Name	62.176.255.210
Port	5060
Reregistration-interval am Provider (s)	600

Provider Proxy

IP Adresse/Host-Name	62.176.255.210
Port	5060

Provider-Outbound-Proxy

Provider Outbound Proxy verwenden	no
IP Adresse/Host-Name	0.0.0.0
Port	0

Provider-inbound-Proxy

Provider Outbound Proxy verwenden	no
IP Adresse/Host-Name	0.0.0.0
Port	0

Provider-STUN

STUN verwenden	no
IP Adresse/Host-Name	empty
Port	3478



CLIP/CLIR

CLIP outgoing in From header - display part:	call number
CLIP outgoing in From header - user part:	call number
Outgoing From Header - domain/host part:	domainName
Diversion: From contains original CallingPartyNumber:	x
Diversion: PAI contains original CallingPartyNumber:	x
CLIP outgoing in P- Asserted-Id header - display part:	call number
CLIP outgoing in P- Asserted-Id header - user part:	call number
CLIP outgoing in P- Preferred-Id header - display part:	omit
CLIP outgoing in P-Preferred-Id header - user part:	omit
CLIP outgoing in Diversion header - display part:	omit
CLIP outgoing in Diversion header - user part:	call number
CLIR outgoing in From header - display part:	anonymous
CLIR outgoing in From header - user part:	fully anonymous
CLIR outgoing Privacy header:	id
COLP / TIP supported for outgoing calls:	COLP supported

Call number formatting

Incoming call - Called party number:	To header user part
Incoming call - Calling party number:	automatic
Incoming call - Type of number (calling):	automatic
Incoming call - Type of number (called):	automatic
Outgoing call - Type of number (calling):	national
Mapping of provider number:	in any case
CLIP no Screening support:	CLIP in From / trusted number inPAI
Call No. with international/national prefix:	yes

Miscellaneous

Media Renegotiation Avoidance:	yes
UseRouteURIAuthentication:	yes
Ignore 100 Rel:	yes
UseViaRPort:	yes
UPDATE Supported:	yes
Session Timer support:	not active
Send automatic 183 response timer (sec):	0
UDP-Keep Alive:	UdpKeepAliveON



Partner der WOBCOM für Kommunikationssysteme

Termath AG

Beesestraße 1
38446 Wolfsburg
Telefon 05361/8500 – 0
info@termath.de

Fenicom GmbH

Am Hafen 36
38112 Braunschweig
Telefon +49 (5 31) 120 55-0
Telefax +49 (5 31) 120 55-25
info@fenicom.de

primary connection it-systemhaus gmbh&co.kg

Heinrich Nordhoff Straße 101
38440 Wolfsburg
Telefon 05361 890790
Telefax 05361 8907919
info@primary-connection.de

Erfahrungen

Aus langjährigen und engen Kontakt zu unseren Kunden, sind Erfahrungswerte und Knowhow im Umgang mit den verschiedenen Telefonanlagen und Systeme gewachsen. Diese folgenden Systeme wurden bereits erfolgreich an unserem Anschluss installiert.

Unify Openscape business





Bintec Elmeq Be Ip Plus(Pbx)



Innovaphone (alle Geräte)



Auerswald Commander 6000

